

## Line Interactive UPS

### Features:

Simple, compact and generous machine appearance  
 Super wide mains input range  
 Excellent microprocessor to ensure reliable operation  
 Automatic adjustment of the AC mains power boost, step-down, stable voltage output  
 Mains restart function  
 Output modified sine wave  
 Automatic charge in off-mode  
 Cold start function  
 Compatible generators

### Application:

1. PC/Fax/Modem
- 2.Small server/Lan
- 3.Cash-counting
- 4.Attendance machine
- 5.Miniature Terminal Equipment
- 6.SOHO Equipment

Line Interactive UPS :						
Model	600VA	1000VA	1200VA	1500VA	2000VA	3000VA
Capacity	600VA /360W	1000VA/480W	1200VA/720W	1500VA /900W	2000VA /1200W	3000VA /1600W
Input						
Voltage	220VAC					
AC Mains Input Voltage Range	145-280 VAC					
Frequency	50/60 Hz					
Output						
Voltage Range(Battery Mode)	±10%					
Frequency Range(Battery Mode)	50/60HZ±1HZ (Adaptive)					
Transfer Time	Normally 2–6ms, no more than 10ms					
Waveform(Battery)	Modified sine wave					Pure sine wave
Battery						
Battery Type & Quantity	12V7Ah x 1	12V 9Ah x 1	12V 7Ah x 2	12V 9Ah x 2	12V 9Ah x 2	12 V 7 Ah x4
Battery Charging Tiime	6 hours charge to 90%					4 hours charge to 90%
LED Indicators						
AC Mode	Green light					Display AC or Load capacity
Battery Mode	Red light flash					Display battery capacity
Audible Alarm						
Battery Mode	Alarm beeps every six seconds					
Low Battery	Alarm beeps every second					
Overload	Alarm beeps twice every second					
Fault	Alarm beeps continuously					
Protection Function						
Comprehensive Protection	Overload, deep discharge and over-charge protection					
Environment						
Temperature And Humidity	Relative humidity 0-90% and temperature 0- 40°C (No-condensing)					
Noise	less than 40dB at one meter distance					
Physical Function						
Dimensions D X W X H (mm)	335x87x143	312x122x195	312x122x195	360x122x195	360x122x195	405x144x213
Net Weight (kgs)	4.4	6.9	8.4	11	12.3	17.6